


PVP™ X6IP



PVP™ X6IP is an outdoor-rated video panel sporting an IP65 rating and brilliant weather-proof SMD2623 LEDs with a pixel pitch of 6.9 mm. With 4,500 NITS, your video image will stand out even in broad daylight. Flexibility of use is optimized by an advanced die-cast aluminum housing, magnetic modules for quick serviceability, and a blow-through design that has an 8% transparency to increase safety in outdoor applications. The innovative design includes sealable louvers, which gives you the option to close them to block back light when used indoors.

FEATURES

- 6.9 mm pixel pitch modular video panel with SMD 2623 LEDs
- Stainless steel hardware is integrated into each panel for secure interlocking between panels
- Solid aluminum die-cast construction makes these panels durable for the touring/rental market
- Magnetic LED modules make replacing them fast and painless in the field or on the repair bench
- Tri-color, full black body LEDs provide the highest in class contrast and black levels
- Computer guided CNC cutting provides ultimate precision for seamless modular connections
- Works with VIP™ Driver and VIP™ Signal Distributor
- Use with the X-series Rig Bar to hang the panels, or with the M12 mounting points on the back of each panel
- IP65 for temporary outdoor/wet use

SPECIFICATIONS

- Control Protocol: LINSN
- Data Connectors: Seetronic® Etherkon® IP65
- Light Source: 5,184 LEDs (tri-color RGB) SMD 2623, 50,000 hours life expectancy
- Color Wavelength: red (625 nm), green (525 nm), blue (470 nm)
- Pixels: 72 x 72
- Pixel Pitch: 6.9 mm
- Pixel Density: 20,736/m²
- Viewing Angle: 130°
- Display Refresh Rate: 3,120 Hz
- Transparency: 8%
- Illuminance: 4,500 NITS
- IP Rating: IP65, temporary outdoor/wet use
- Cable Length (signal extension): 2.46 ft (0.75 m)
- Cable Length (power): 6 ft (1.83 m)
- Cable Length (power extension): 2.46 ft (0.75 m)
- Power Connection: Edison plug to Seetronic® Powerkon®
- Power Input: Seetronic® Powerkon®
- Power Output: Seetronic® Powerkon®
- Power Linking: 12 units @ 120 V; 20 units @ 208 V; 22 units @ 230 V
- Maximum Panels/VIP™ Driver: 120
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 160 W, 1.33 A @ 120 V, 60 Hz
- Power and Current: 160 W, 0.77 A @ 208 V, 60 Hz
- Power and Current: 160 W, 0.70 A @ 230 V, 50 Hz
- Weight: 19.8 lb (9 kg)
- Dimensions: 19.7 x 3.27 x 20.35 in (500 x 83 x 517 mm)
- Housing Material: Aluminum die-cast
- Compatible Mounting Options: X Series™ Rig Bar (RB-X50CM, RB-X200CM), or M12 Bolt/Clamp (rear mounting)
- Accessories (required): VIP™ Driver
- Accessories (optional): VIP™ Signal Distributor
- Accessories (optional): VIP™ Media Server Pro
- Accessories (optional): VIP™ 5162b Signal Processor
- Approvals: CE